

Outdoor unit		RAV-SP562AT-E	RAV-SP802AT-E	RAV-SP1102AT-E	RAV-SP1402AT-E
Indoor unit (Ceiling)		RAV-SM562CT-E	RAV-SM802CT-E	RAV-SM1102CT-E	RAV-SM1402CT-E
Cooling capacity	kW	5.0	7.1	10.0	12.5
Cooling range (min. - max.)	kW	2.2 - 5.6	2.2 - 8.0	3.0 - 12.0	3.0 - 14.0
Power input (min. - rated - max.), cooling	kW	0.50 - 1.41 - 1.90	0.50 - 2.10 - 2.70	0.65 - 2.40 - 4.20	0.65 - 3.90 - 4.70
EER, cooling	W/W	3.55	3.38	4.17	3.21
Energy efficiency class, cooling		A	A	A	A
Annual energy consumption, cooling	kWh	705	1050	1200	1950
Heating capacity	kW	5.6	8.0	11.2	14.0
Heating range (min. - max.)	kW	2.2 - 7.0	2.2 - 10.0	3.0 - 13.0	3.0 - 16.5
Power input (min. - rated - max.), heating	kW	0.50 - 1.50 - 2.30	0.50 - 2.20 - 3.10	0.65 - 2.50 - 4.0	0.65 - 3.75 - 4.60
COP, heating	W/W	3.73	3.64	4.48	3.73
Energy efficiency class, heating		A	A	A	A

DI - Technical specifications **heat pump**

Outdoor unit		RAV-SM562AT-E	RAV-SM802AT-E	RAV-SM1102AT-E	RAV-SM1402AT-E
Indoor unit (Ceiling)		RAV-SM562CT-E	RAV-SM802CT-E	RAV-SM1102CT-E	RAV-SM1402CT-E
Cooling capacity	kW	5.0	7.0	10.0	12.3
Cooling range (min. - max.)	kW	1.5 - 5.6	1.5 - 8.0	3.0 - 11.2	3.0 - 13.2
Power input (min. - rated - max.), cooling	kW	0.45 - 1.82 - 1.95	0.50 - 2.53 - 2.76	0.60 - 3.51 - 4.10	0.65 - 4.52 - 4.85
EER, cooling	W/W	2.75	2.77	2.85	2.72
Energy efficiency class, cooling		D	D	C	D
Annual energy consumption, cooling	kWh	910	1265	1755	2260
Heating capacity	kW	5.6	8.0	11.2	14.0
Heating range (min. - max.)	kW	1.5 - 6.3	1.5 - 9.0	3.0 - 12.5	3.0 - 16.0
Power input (min. - rated - max.), heating	kW	0.45 - 1.64 - 2.40	0.50 - 2.47 - 3.20	0.60 - 3.20 - 4.10	0.65 - 4.14 - 4.60
COP, heating	W/W	3.41	3.24	3.50	3.38
Energy efficiency class, heating		B	C	B	C

Indoor unit		RAV-SM562CT-E	RAV-SM802CT-E	RAV-SM1102CT-E	RAV-SM1402CT-E
Air flow (h/l)	m ³ /h - l/s	780/600 - 217/167	1110/876 - 308/243	1650/1272 - 458/353	1800/1386 - 500/385
Sound pressure level (h/l)	dB(A)	36/30	38/33	41/35	43/37
Sound power level (h/l)	dB(A)	51/45	53/48	56/50	58/52
Dimensions (H x W x D)	mm	210 x 910 x 680	210 x 1180 x 680	210 x 1595 x 680	210 x 1595 x 680
Weight	kg	21	25	33	33